

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : MasonryDefender Garage Floor Sealer

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Sealing Concrete

1.3. Details of the supplier of the safety data sheet

SaverSystems
800 S 7th St
Richmond, 47374 - U.S.A.
T (800) 860-6327

1.4. Emergency telephone number

Chemtel : 1 (800) 255-3924 24/7

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Eye Irrit. 2A H319

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS07

Signal word (GHS-US) : Warning
Hazard statements (GHS-US) : H319 - Causes serious eye irritation
Precautionary statements (GHS-US) : P264 - Wash hands thoroughly after handling
P280 - Wear protective gloves, eye protection, protective clothing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337+P313 - If eye irritation persists: get medical advice/attention

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Styrene-Acrylic Copolymer - ALBERDINGK® M2955		< 31	Eye Irrit. 2A, H319
Diethylene glycol monobutyl ether	(CAS No) 112-34-5	3 - 5	Flam. Liq. 4, H227 Eye Irrit. 2A, H319
Ethylene glycol	(CAS No) 107-21-1	< 5	Acute Tox. 4 (Oral), H302
Ammonium hydroxide	(CAS No) 1336-21-6	< 0.02	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335

Garage Floor Sealer

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: In all cases of doubt, or when symptoms persist, seek medical advice. Move the affected person away from the contaminated area and into the fresh air.
First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Wash off immediately with soap and plenty of water. Obtain medical attention if irritation persists.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention immediately.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. If the person is fully conscious, make him/her drink water. Never give an unconscious person anything to drink. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May cause an allergic skin reaction. In case of repeated or prolonged exposure : Inhalation of vapours or spray/mists. May be irritating to the mucous membranes and to the respiratory system.
Symptoms/injuries after skin contact	: Repeated or prolonged skin contact may cause dermatitis and defatting.
Symptoms/injuries after eye contact	: In fine dispersion/spraying/misting: Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Use media as appropriate for surrounding material . Foam. Dry powder. Carbon dioxide. Water spray. Sand.
------------------------------	---

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protective equipment for firefighters	: Do not enter fire area without proper protective equipment, including respiratory protection. In case of fire: Wear self-contained breathing apparatus.
Other information	: Hazardous decomposition products may be released during prolonged heating like smokes, carbon monoxide and dioxide, nitrogen oxides (NO _x). Toxic metal oxide smoke.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid inhalation of vapour and spray mist. Avoid skin and eye contact. Ensure adequate ventilation.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Use personal protective equipment as required. Use suitable eye protection and gloves. For further information refer to section 8 : Exposure-controls/personal protection.
Emergency procedures	: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Dispose of contents/container to comply with applicable local, national and international regulations. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Collect all waste in suitable and labelled containers and dispose according to local legislation. For small spills, absorb or cover with dry earth, sand, or other inert non-combustible absorbent material and place into waste containers for later disposal. Ensure all national/local regulations are observed. Collect spills and put it into appropriated container.
-------------------------	--

Garage Floor Sealer

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Surface will become slippery when wet or damp.
- Precautions for safe handling : Keep out of reach of children. Do not breathe Wet misty spray . Wear goggles if splashing or spraying is anticipated. Wear suitable gloves. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
- Hygiene measures : Do not eat, drink or smoke when using this product. Avoid contact with skin and eyes. Wash contaminated clothing prior to re-use. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Use good personal hygiene practices. Separate working clothes from town clothes. Launder separately.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations. A washing facility/water for eye and skin cleaning purposes should be present. Ensure adequate ventilation.
- Storage conditions : Keep locked up and out of reach of children. Keep only in the original container in a cool well ventilated place. Store away from freezing (avoid freezing during storage). Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Keep container closed when not in use. Keep away from food and drink.
- Incompatible materials : Strong acids, bases. Oxidizing agents.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Diethylene glycol monobutyl ether (112-34-5)

USA ACGIH	ACGIH TWA (ppm)	10 ppm
-----------	-----------------	--------

8.2. Exposure controls

- Appropriate engineering controls : Ensure adequate ventilation. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
- Personal protective equipment : Gloves. Protective clothing. Protective goggles. Avoid all unnecessary exposure. For certain operations, additional Personal Protection Equipment (PPE) may be required.



- Hand protection : Protective water resistant gloves.
- Eye protection : Wear chemical splash goggle.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : Work in well-ventilated zones or use proper respiratory protection. In case of insufficient ventilation, wear suitable respiratory equipment.
- Environmental exposure controls : Avoid discharge to the environment.
- Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Clear
- Color : Colourless
- Odor : Slight sweet odor
- Odor threshold : No data available
- pH : 7.5
- Relative evaporation rate (butyl acetate=1) : No data available
- Melting point : No data available

Garage Floor Sealer

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Freezing point	: < 0 °C (<32 °F)
Boiling point	: > 100 °C (>212 °F)
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.01 g/cm ³ (8.5 lb/gal)
Solubility	: Water: Soluble
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Extremely high or low temperatures.

10.5. Incompatible materials

Strong oxidizers. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Hazardous decomposition products may be released during prolonged heating like smokes, carbon monoxide and dioxide, NO_x. Emits toxic fumes under fire conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified
(Based on available data, the classification criteria are not met)

Ammonium hydroxide (1336-21-6)	
LD50 oral rat	350 mg/kg
ATE (oral)	350.000 mg/kg bodyweight

Diethylene glycol monobutyl ether (112-34-5)	
LD50 oral rat	3384 mg/kg
LD50 dermal rabbit	2700 mg/kg
ATE (oral)	3384.000 mg/kg bodyweight
ATE (dermal)	2700.000 mg/kg bodyweight

Skin corrosion/irritation : Not classified
(Based on available data, the classification criteria are not met)
pH: 7.5

Garage Floor Sealer

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Serious eye damage/irritation	: Causes serious eye irritation. pH: 7.5
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
Specific target organ toxicity (single exposure)	: Not classified (Based on available data, the classification criteria are not met)
Specific target organ toxicity (repeated exposure)	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Symptoms/injuries after inhalation	: May cause an allergic skin reaction. In case of repeated or prolonged exposure : Inhalation of vapours or spray/mists. May be irritating to the mucous membranes and to the respiratory system.
Symptoms/injuries after skin contact	: Repeated or prolonged skin contact may cause dermatitis and defatting.
Symptoms/injuries after eye contact	: In fine dispersion/spraying/misting: Causes serious eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ammonium hydroxide (1336-21-6)	
LC50 fishes 1	8.2 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 Daphnia 1	0.66 mg/l (Exposure time: 48 h - Species: water flea)
EC50 Daphnia 2	0.66 mg/l (Exposure time: 48 h - Species: Daphnia pulex)

Diethylene glycol monobutyl ether (112-34-5)	
LC50 fishes 1	1300 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	2850 mg/l (Exposure time: 24 h - Species: Daphnia magna)
EC50 other aquatic organisms 1	> 100 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)
EC50 Daphnia 2	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and degradability

MasonryDefender Garage Floor Sealer	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

MasonryDefender Garage Floor Sealer	
Bioaccumulative potential	Not established.

Diethylene glycol monobutyl ether (112-34-5)	
BCF fish 1	(no bioconcentration expected)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

Garage Floor Sealer

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose containers to flames, sparks, heat, or other potential ignition sources. Do not re-use empty containers. It is the responsibility of the user to determine if disposal material is hazardous according to federal, state and local regulations. Ensure all national/local regulations are observed.
- Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

- In accordance with DOT
No dangerous good in sense of transport regulations

Additional information

- Other information : No supplementary information available.

ADR

- Transport document description : No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

MasonryDefender Garage Floor Sealer	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	5000000 lb
Ammonium hydroxide (1336-21-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	1000 lb
Diethylene glycol monobutyl ether (112-34-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA. Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

15.2. International regulations

CANADA

MasonryDefender Garage Floor Sealer	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Ammonium hydroxide (1336-21-6)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Class E - Corrosive Material
Diethylene glycol monobutyl ether (112-34-5)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects

EU-Regulations

Ammonium hydroxide (1336-21-6)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.	

Garage Floor Sealer

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Diethylene glycol monobutyl ether (112-34-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

Classification according to Directive 67/548/EEC or 1999/45/EC

Xi; R36

Full text of R-phrases: see section 16

15.2.2. National regulations

Ammonium hydroxide (1336-21-6)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Poisonous and Deleterious Substances Control Law
Listed on the Canadian Ingredient Disclosure List

Diethylene glycol monobutyl ether (112-34-5)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on Industrial Safety and Health Law Substances (ISHL)
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on the Canadian Ingredient Disclosure List

15.3. US State regulations

Ethylene Glycol (107-21-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
	Yes			

SECTION 16: Other information

Indication of changes : All requirement according to the federal final rule of hazard communication revised on 2012 (HazCom 2012) has been applied.

Sources of Key data : Supplier's Safety Data Sheet.

Other information : None.

Full text of H-phrases: see section 16:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 4	Flammable liquids Category 4
Skin Corr. 1B	Skin corrosion/irritation Category 1B
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H227	Combustible liquid
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation

Garage Floor Sealer

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product